

OscarsPro

2 MP Dome Camera



OPC-11B1

2 MP Dome Camera OPC-11B1

Ethernet	1 x RJ45 10M/100M
Video Compression	H.264/MJPEG
Image Sensor	1 /2.7 progressive scan CMOS
Lens Type	Varifocal Lens 2.7 -12mm Acceptance of $\pm 10\%$
Resolution	1280 x 960
Signal/ Noise Ratio	>55dB
Minimum Illumination	0.01 Lux@F1.2 B/W: 0Lux with IR on
IR Distance	30 Mtr
Shutter Speed	Auto/Manual 1s ~ 1/100000s
Bandwidth	32Kbps ~ 8192Kbps
Noise Reduction	3D DNR
Video Streaming	Dual Stream Primary: 1.3MP /1MP (1~25/30fps) Secondary: D1/CIF (1~25/30fps)
Audio Compression	G.711a/ G.711u
Resolution	1280×960), 720P(1280×720), D1(704×576/704×480), CIF(352×288/352×240)
Alarm I/O	1:1
Privacy Masking	Up to 4 Areas
Audio I/O	1:1
Day & Night(ICR)	Automatic Gain Control, White Balance, Electronic Day & Night(ICR)
Viewing Angle	H:101°~31°, V:54°~17°
Wide Dynamic Range	Supported
Supported Protocols	IPv4/IPv6, HTTP, HTTPS,TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, ONVIF
Event Trigger	Motion Detection, Network Disconnection, External Input, Audio Alarm, Pre/Post Alarm Buffer
Network	IPV4 and IPV6
System Capability	ONVIF Profile G,S,T
Accessibility	20 Users simultaneously
Storage	MicroSD up to 128GB
IP Rating	IP67
Vandal Resistance	IK10
Power Consumption	4W Max
Power Parameters	PoE (802.3af)/ DC 12V \pm 10%
Environmental	40°C~60°C, Humidity :0~90%(Non-condensing)