

OscarsPro

CHAIRMEN & DELEGATE UNIT

"Best audio quality for video conferencing"



Model : OS-MIC-1001

Chairmen Unit - OS-MIC-1001

Frequency response Sensitivity	80Hz~16KHz
Maximum SPL	-46dBV/Pa
SNR	125dB (THD>3%)
THD	>80dB(A)
Installation	<0.1%
Inter Connectivity	Desktop
Headphone load	Digital Loop-In/Loop-Out
Headphone jack	16-32Ω
LED indication for Mute/Unmute	3.5mm
Connector	Supported
Microphone input impedance	With 1.8m 6-pin aviation connector
Microphone type	1KΩ
Microphone directionality	Microphone type
Maximum headphone volume	Cardioid directionality
Maximum power consumption	40mW
Built in Speakers	3 W
Mic Button	volume adjustment
Priority Button	Touch Button to enable/disable microphone
Built-in DSP	Touch Button for priority function to turn off all delegate units that are speaking
Audio Output	Built-in DSP audio processor with 48KHZ sampling rate to provide clear and bright
Power supply	sound 3.5 mm output sockets with Volume adjustment slider

Delegate Unit - OS-MIC-1010

Maximum SPL	Controller power supply 125dB (THD>3%)
-------------	--

Sensitivity	-46dBV/Pa
Headphone jack	3.5mm
Connector	With 1.8m 6-pin aviation connector
THD	<0.1%
Microphone type	Electret capacitive
Microphone input impedance	1K Ω
Microphone directionality Maximum	Cardioid directionality
headphone volume Frequency	40mW
response	80Hz~16KHz
SNR	>80dB(A)
Maximum power consumption Mic	3 W
Button	Touch Button to enable/disable microphone
Headphone load	16-32 Ω
LED indication for Mute/Unmute Inter	Supported
Connectivity	Digital Loop-In/Loop-Out
Built in Speakers	Speaker with volume adjustment
Audio Output	3.5 mm output sockets with Volume adjustment slider
Installation	Desktop
Built-in DSP	Built-in DSP audio processor with 48KHZ sampling rate to provide clear and bright sound
Power supply	Controller power supply

Central Conference - OS-MIC-1008

Audio Output	1x XLR LINE Out, 1 x RCA line Out
Audio Input	1x XLR LINE In, 1 x RCA line In
Number of Channels	16CH

Open Microphone	up to 8 wired microphones opened at the same time
SNR	>85dB(A)
Total Harmonic Distortion	<0.05%
Microphone capacity	Minimum up to 500 Wired Microphone Unit and 300 wireless Units
Microphone management modes	FIFO/NORMAL/VOICE (voice control)/APPLY
Frequency Response	20Hz~20KHz
Control Display	Inbuilt 4.3-inch TFT colourful touch screen to control the device
Dynamic Range	>80dB
Output Load	>1K Ω
Extension Port	1 RJ 45 Extension port to Connect to the extension controller
Control Port	1x Alarm, 1x RS485, 1x RJ45 PC control, 2x RS232 Serial Port
LAN Interface	1xRJ45 Network Port
PTZ Camera control	PTZ camera controlling for Voice tracking functionality
Delegate interconnectivity	4 Nos of 6-pin aviation connector
USB interface	USB x1 for Record/playback
Amplifier Output	2x25W/4 Ω
Static power consumption	30W
Output power consumption	320W